

The Conceptual Design of TiO₂/SiO₂ Photonic Crystal Heterostructures: Principles for Improved Optical and Photocatalytic Performance

Zichang Chen

Shanghai Guanghua Qidi College, Shanghai, 20433, China

Email: 15821572761@163.com

Manuscript received August 1, 2026; accepted September 3, 2026; published October 27, 2026

Abstract—With the growing demand for renewable energy and environmental remediation, there is a need for higher-performance photocatalysts and better light-harvesting strategies. In addition, TiO₂ photocatalysts have been widely studied due to their stability, low cost, and non-toxicity. However, their performance is limited by weak light absorption and fast recombination of photogenerated electron-hole pairs. Thus, it is essential to design materials that improve light harvesting and promote charge separation simultaneously. This paper investigates the design, fabrication, and applications of a photonic crystal heterostructure consisting of an ultrathin anatase TiO₂ film sandwiched between two thick SiO₂ layers. Particular attention is given to the role of self-assembly, photonic bandgap engineering, and interfacial chemical bonding in boosting photocatalytic performance. The results show that the SiO₂/TiO₂/SiO₂ integrates the advantages of both photonic crystals and semiconductor heterojunctions. And this is achieved through the periodic refractive-index contrast between TiO₂ and SiO₂, which generates tunable photonic bandgaps and slow-light effects, thereby enhancing light confinement and photon absorption. Besides, Ti-O-Si interfacial bonding stabilizes the structure and promotes electron-hole separation, while self-assembly offers a simple, low-cost route to ordered nanostructures.

Keywords—photonic crystal heterostructure, Titanium Dioxide (TiO₂), Silicon Dioxide (SiO₂), self-assembly, photocatalysis

I. INTRODUCTION

Under rapid advances in optoelectronics and increasing environmental pressure, the enhancement of light utilization and photocatalytic efficiency has become essential [1, 2]. At the same time, TiO₂, especially anatase-phase TiO₂, is widely used in photocatalysis due to its excellent activity under ultraviolet light for pollutant degradation and water splitting [1-3]. However, its intrinsic limitations, including weak visible-light absorption and rapid recombination of photogenerated electron-hole pairs, severely limit overall efficiency [1, 4]. Accordingly, existing strategies mainly include doping to extend light absorption, coupling with narrow-bandgap semiconductors or carbon materials to facilitate charge separation, and creating nanostructures to increase surface area and light capture. These methods often target only one aspect and lack a combined design for light management and interfacial charge control. As a solution, photonic crystals, with periodic refractive index patterns, can create photonic bandgaps and slow-light effects, enhancing light localization and extending the optical path, thus enhancing light absorption [5-7]. By periodically integrating high-refractive-index TiO₂ with low-refractive-index SiO₂, optical field manipulation and interfacial charge regulation

can be simultaneously achieved within a unified system [8, 9]. Based on molecular engineering and structural design principles, this paper explores the conceptual design of TiO₂/SiO₂ photonic crystal heterostructures, with emphasis on light-field enhancement and charge separation arising from refractive-index periodicity and Ti-O-Si interfacial bonding. In addition, theoretical optimization strategies and potential applications are proposed, offering guidance for designing high-efficiency photocatalysts and visible-light-responsive systems.

II. FUNDAMENTAL PRINCIPLES OF MOLECULAR ENGINEERING

The design of TiO₂/SiO₂ photonic heterostructures follows key molecular engineering principles, enabling precise control of nanoscale ordering, interfacial bonding, and optical properties to boost photocatalytic efficiency.

A. Self-Assembly for Ordered Nanostructure Formation

Through self-assembly, ordered nanostructures can be constructed through a key bottom-up strategy [8, 10]. During this process, colloidal SiO₂ and TiO₂ nanoparticles can spontaneously organize into periodic photonic crystal structures through methods such as vertical deposition, sol-gel processing, and electrophoretic assembly [8]. And this approach enables control over particle packing and film thickness, allowing the formation of well-defined nanoscale ordering.

To improve structural uniformity, surface modification of nanoparticles is often used. By tuning surface charge and interparticle interactions, this modification promotes more regular packing and improves long-range structural order [8, 10]. Compared with top-down lithography, self-assembly enables scalable fabrication of large-area ordered structures with relatively simple processing routes. Importantly, this ordering process serves as the structural basis for subsequent photonic modulation and interfacial functionalization in the heterostructure design. The final morphology strongly relies on nanoparticle arrangement, which determines the periodicity of the resulting multilayer system.

B. Photonic Bandgap and Light Confinement Mechanism

Photonic crystals are formed by periodic media with alternating refractive indices. In the TiO₂/SiO₂ system, the refractive-index contrast between TiO₂ with a refractive index of 2.4 and SiO₂ with a refractive index of 1.45 induces Bragg diffraction, leading to the formation of photonic bandgaps at specific wavelength ranges [5, 7]. Near the bandgap edges, the dispersion relation becomes strongly

flattened, thus resulting in slow-light behavior and a reduced group velocity. This effect enhances the optical dwell time inside the periodic structure and strengthens light-matter interaction in the high-index regions [6, 7].

As a result, light propagation is redistributed between allowed and forbidden modes, enabling spectral selectivity and efficient control of photon transport in periodic dielectric systems. Photonic bandgap formation thus provides a fundamental mechanism for manipulating light propagation in refractive-index-modulated media. This optical response establishes the basis for understanding structure-dependent light distribution in multilayer heterostructures.

C. Interfacial Heterojunctions and Chemical Bonding Effects

The formation of $\text{TiO}_2/\text{SiO}_2$ heterojunction interfaces gives rise to newly developed electronic and chemically distinct environments that significantly govern and modulate interfacial charge-transfer behavior [9, 10]. At the atomic scale, Ti-O-Si bonds connect the two components, modifying local electronic structure and enabling interfacial charge redistribution. This interfacial coupling provides pathways for directional charge transfer across the interface, thereby modifying carrier separation dynamics at the junction. Besides, the modified surface chemistry influences interfacial adsorption behavior and reaction site accessibility, particularly in aqueous environments.

Moreover, $\text{TiO}_2\text{-SiO}_2$ composite interfaces often exhibit superhydrophilic characteristics, which enhance surface wetting and facilitate mass transport at the solid-liquid interface [2, 11]. As a result, these interfacial chemical and surface properties determine the reaction environment at the material boundary and govern interfacial reactivity and stability.

III. THE STRUCTURAL DESIGN AND FABRICATION OF $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ HETEROSTRUCTURES

The proposed engineering solution is a multilayer $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ photonic crystal heterostructure [7, 8]. While $\text{TiO}_2/\text{SiO}_2$ is used in a general sense to describe the material system, $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ denotes the symmetric multilayer configuration used for optical confinement.

A. Multilayer Structural Design and Optical Function

The $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ heterostructure is constructed as a multilayer photonic platform with a clearly defined spatial configuration of functional layers [5, 7]. In this configuration, a thick SiO_2 layer is first introduced as a supporting and insulating framework, providing structural stability for subsequent deposition processes.

Accordingly, an ultrathin anatase TiO_2 film is positioned as the central active layer, thus forming a confined functional region embedded between dielectric boundaries. In this way, this spatial arrangement enables the TiO_2 layer to function as a resonant defect within the multilayer architecture. The surrounding layers confine the TiO_2 region, thereby establishing well-defined boundaries that govern field distribution across the stack [12]. Layer thickness and stacking sequence determine the resonance condition, allowing spatial confinement of optical modes within the active layer.

In addition, asymmetry in local thickness variation can introduce tunability in resonance position without altering material composition. This geometric control provides a direct route to adjust modal localization within the confined TiO_2 region. Such a design strategy also enhances sensitivity of the optical response to nanoscale structural variations.

B. Interfacial Mechanisms and Photonic Effects

The performance enhancement of $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ heterostructures is governed by the synergistic interaction between interfacial chemistry and photonic modulation. At the interface, Ti-O-Si bonding defines the electronic coupling pathway across the material boundary, affecting charge redistribution at the heterojunction and stabilizing interfacial states under excitation [2].

Within the same architecture, the periodic dielectric environment controls the spatial distribution of incident light across the multilayer structure. This redistribution determines where photoexcitation is preferentially generated within the TiO_2 region, linking optical field localization with interfacial carrier dynamics. In addition, the degree of spatial overlap between high-intensity optical regions and interfacial bonding sites becomes a key factor affecting carrier utilization efficiency. Local variations in field intensity can therefore lead to non-uniform excitation density across the TiO_2 layer. This spatial non-uniformity further affects the likelihood of carriers participating in interfacial processes. As a result, the overall response of the system is not governed by a single process but by the spatial overlap between light distribution and interfacial charge transport pathways, which jointly determine the efficiency of carrier utilization [5].

C. Fabrication Methods and Assembly Strategies

Using a combination of bottom-up assembly and thin-film deposition techniques, $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ heterostructures are fabricated, enabling controlled construction of multilayer architectures in terms of thickness and sequence [7, 8]. In this process, the SiO_2 layers are typically prepared by sol-gel processing or nanoparticle assembly to form continuous dielectric films. These processes allow uniform coverage and provide a stable framework for subsequent layer deposition [10]. Moreover, the TiO_2 layer is deposited using physical or chemical methods like sputtering, spin coating, or Atomic Layer Deposition (ALD), followed by thermal treatment to obtain the anatase phase. Depending on the deposition route, film continuity, grain size, and surface roughness can be adjusted, which directly affects the uniformity of the deposited layer.

In addition, interfacial adhesion between adjacent layers is influenced by deposition environment and precursor chemistry, which can influence layer continuity during thermal processing. Therefore, careful control of deposition sequence and annealing conditions is required to ensure reproducible multilayer formation. Hybrid approaches that combine colloidal assembly with thin-film deposition enable multilayer integration under relatively flexible processing conditions. Process parameters such as deposition rate, particle dispersion, and annealing temperature critically influence layer continuity and structural reproducibility [8, 10].

IV. SYNERGISTIC PROPERTIES AND THEIR IMPLICATIONS FOR APPLICATIONS AND CHALLENGES

A. Synergistic Photonic and Interfacial Effects

The $\text{TiO}_2/\text{SiO}_2$ heterostructure integrates optical modulation and interfacial functionality within a single multilayer architecture. This is derived from the cooperative contribution of periodic dielectric structuring and chemically defined interfaces [2, 5].

Compared with conventional TiO_2 thin films, the heterostructure exhibits more efficient utilization of incident photons and more effective carrier utilization within the active region. The multilayer configuration improves spatial distribution of optical excitation, while the interface design stabilizes charge transport pathways across adjacent layers. In addition, the SiO_2 framework provides structural support that helps maintain integrity of the multilayer stack under processing and operation conditions [8]. The system advantage arises from the coordinated effect of structural arrangement and interface design rather than a single functional component.

B. Application Prospects and Constraints

The $\text{TiO}_2/\text{SiO}_2$ heterostructure enables controlled light utilization and surface-driven reactions. For example, it is applied in photocatalytic water splitting, wastewater purification, and environmental pollutant degradation [1, 2]. Besides, the structure is relevant to UV detection, optical filtering, and compact photonic components, where spatial control of optical response is required [6, 7].

Despite these advantages, practical implementation is limited by fabrication requirements. Notably, multilayer uniformity, thickness precision, and long-range ordering remain challenging, especially for scalable production. In addition, the reliance on UV-active TiO_2 restricts spectral utilization, and further material engineering is required to extend functionality toward visible-light conditions, as shown in Table 1 [1, 3, 11].

Table 1. Comparison of properties between pure TiO_2 thin film and $\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ heterostructure

Property	Pure TiO_2 Thin Film	$\text{SiO}_2/\text{TiO}_2/\text{SiO}_2$ Heterostructure
Light utilization	Limited absorption range	Improved utilization via multilayer design
Photocatalytic performance	Moderate activity	Enhanced overall reaction efficiency
Carrier utilization	High recombination loss	Reduced loss through interfacial architecture
Structural stability	Prone to cracking	Stabilized by SiO_2 framework
Fabrication complexity	Simple process	Multilayer process with strict control
Scalability	Relatively easy	Limited by structural precision
Cost	Low	Higher due to nanoscale engineering

V. CONCLUSION

This paper reveals that embedding ultrathin anatase TiO_2 films between thick SiO_2 layers enables the construction of an advanced photonic crystal heterostructure with greatly enhanced optical and photocatalytic performance. And the synergistic integration of self-assembly, molecular engineering, and heterojunction design leads to improved

light trapping, more efficient electron-hole separation, and favorable surface properties, thereby strengthening light-matter interactions compared with conventional TiO_2 photocatalysts. Despite these advantages, the fabrication process requires precise nanoscale ordering and strict control of layer thickness, which increases experimental complexity, while the scalability of highly ordered structures remains challenging for large-area production. Future effort should thus prioritize the development of visible-light-active materials, scalable and economically viable fabrication methods, and more sophisticated nanoscale engineering strategies. With continued progress in these directions, $\text{TiO}_2/\text{SiO}_2$ photonic heterostructures may offer wider applications for environmental, energy, and optoelectronic technologies.

CONFLICT OF INTEREST

The author declares no conflict of interest.

REFERENCES

- [1] X. Chen and S. S. Mao, "Titanium dioxide nanomaterials: Synthesis, properties, modifications, and applications," *Chemical Reviews*, vol. 107, no. 7, pp. 2891–2959, 2007. doi: 10.1021/cr0500535.
- [2] A. Fujishima, X. Zhang, and D. A. Tryk, " TiO_2 photocatalysis and related surface phenomena," *Surface Science Reports*, vol. 63, no. 12, pp. 515–582, 2008. doi: 10.1016/j.surfrep.2008.10.001.
- [3] M. Rafique, "Hydrogen Production Using TiO_2 -Based Photocatalysts: A Comprehensive Review," *ACS Omega*, vol. 8, no. 29, pp. 25640–25648, 2023. doi: 10.1021/acsomega.3c00963.
- [4] C. J. Querebillo, "A Review on Nano Ti-Based Oxides for Dark and Photocatalysis: From Photoinduced Processes to Bioimplant Applications," *Nanomaterials*, vol. 13, no. 6, 982, 2023. doi: 10.3390/nano13060982.
- [5] J. D. Joannopoulos, S. G. Johnson, J. N. Winn, and R. D. Meade, *Photonic Crystals: Molding the Flow of Light*, 2nd ed. Princeton, NJ, USA: Princeton University Press, 2008.
- [6] T. Raja-Mogan, B. Ohtani, and E. Kowalska, "Photonic Crystals for Plasmonic Photocatalysis," *Catalysts*, vol. 10, no. 8, 827, 2020. doi: 10.3390/catal10080827.
- [7] R. S. Dubey, P. Sharma, and R. Singh, "Photonic band gap analysis of 1D $\text{TiO}_2/\text{SiO}_2$ photonic crystals using plane wave method for thin film solar cell applications," *IOP Conference Series: Materials Science and Engineering*, vol. 1263, 012007, 2022. doi: 10.1088/1757-899X/1263/1/012007.
- [8] H. Li, Y. Zhang, and X. Chen, "Rapid preparation of TiO_2 - SiO_2 heterostructure photonic crystal in the near-infrared region via a modified electrophoresis-assisted self-assembly process," *Materials Chemistry and Physics*, vol. 214, pp. 77–85, 2018.
- [9] Y. Wang, "A Self-Assembly-Prepared TiO_2 - SiO_2 Heterostructure Film with Enhanced Photocatalysis Activity," *Applied and Computational Engineering*, vol. 123, pp. 59–65, 2025.
- [10] S. Pal, A. Taurino, M. Catalano, and A. Licciulli, "Block Copolymer and Cellulose Templated Mesoporous TiO_2 - SiO_2 Nanocomposite as Superior Photocatalyst," *Catalysts*, vol. 12, no. 7, 770, 2022. doi: 10.3390/catal12070770.
- [11] Y. Wei, Q. Wu, H. Meng, Y. Zhang, and C. Cao, "Recent advances in photocatalytic self-cleaning performances of TiO_2 -based building materials," *RSC Advances*, vol. 13, pp. 20584–20597, 2023. doi: 10.1039/D2RA07839B.
- [12] H. Wu, L. Li, S. Wang, N. Zhu, Z. Li, L. Zhao, and Y. Wang, "Recent advances of semiconductor photocatalysis for water pollutant treatment: mechanisms, materials and applications," *Physical Chemistry Chemical Physics*, vol. 25, pp. 25899–25924, 2023. doi: 10.1039/D3CP03391K.

Copyright © 2026 by the authors. This is an open access article distributed under the Creative Commons Attribution License which permits unrestricted use, distribution, and reproduction in any medium, provided the original work is properly cited ([CC BY 4.0](https://creativecommons.org/licenses/by/4.0/)).